

iNAT-MSLG-5 • iNAT-MSLG-5-DA

Inertial Measuring System for Navigation, Stabilization and Surveying Applications
with optional Dual-Antenna True Heading Capability

iNAT-MSLG-5 is part of the IMS product family of systems with true heading capability for inertial navigation, surveying, guidance and stabilization and dynamically motion analysis with advanced MEMS gyros, that covers applications, which require high accuracy, reliability, a flexible interface and easy integration and usage.

- High performance inertial navigation and surveying system for airborne, naval, underwater, surface and railway applications; supports dual-antenna GNSS based true north seeking also at standstill condition.
- MEMS technology with low angular random walk and high angular and accel. resolution.
- Integrated multi-constellation capable GPS / GLO / GAL / BDS etc. RTK capable GNSS engine with single or dual antenna.
- Internal 32 GByte data storage for black-box operation capability (option: 128 GByte)
- High data rate up to 500 Hz, open interfaces: Ethernet TCP/IP - UDP, CAN, UART RS422/RS232, ARINC429, ARINC825, NMEA 183.
- Integrated VMS / odometer interface.
- Small size, low weight, low power; integrated surveying markers and aiding support points on the enclosure (to support also advanced surveying applications).

The iNAT-MSLG consists of three high accurate MEMS based gyroscopes, three servo accelerometers, a powerful strapdown processor and an open and modular architecture, which allows also adaptations to customer's demands.

The system contains an up to all frequency all constellation RTK capable GNSS receiver (GPS, GLONASS, GALILEO, Beidou), several Dig-I/Os (e.g. for odometer, laser altimeter, DVL). Communication I/Os are RS422/232 UART, Ethernet (TCP/IP, UDP), ARINC429, CAN, ARINC825 as well as internal data storage on non-volatile memory.

Data processing (strapdown navigation, gyro compassing, north keeping or motion monitoring) is performed inside of the iNAT-MSLG, and also data transmission and storage of pure or corrected raw data is available.

The iNAT-MSLG-5 allows true heading determination in-motion and with dual-antenna setup iNAT-MSLG-5-DA also during standstill within significant less than 3 minutes (at warm-start < 90 seconds).

For surface applications the most sophisticated, wheel sensor supported data fusion provides



also highest position accuracy even when the system suffers significant GNSS outages (advanced dead-reckoning).

The iNAT-MSLG contains a robust INS/GNSS based data fusion, using iMAR's highly sophisticated 42+ state Kalman filtering incl. free inertial and dead-reckoning navigation support. Beside of robustness and superior accuracy the very small data latency and jitter makes the iNAT-MSLG the convincing choice also for advanced vehicle and antenna control applications.

The GUI / HMI software iXCOM as well as direct access allow the user full control of the system as well as data storing and to perform maintenance activities also via network (e.g., download of stored data). Furthermore, a powerful post-processing tool is available for advanced surveying applications.

The iNAT-MSLG is fully interface compatible to all other systems of the iNAT family, e.g. iNAT-FSLG, iNAT-FSSG (FOG based) or iNAT-RQT, iNAT-RQH (RLG based).

The system is not covered by any ITAR regulations or any other export control.



Technical Data of iNAT-MSLG-5 and iNAT-MSLG-5-DA (rms values)

Data Output:	Heading, Roll, Pitch, Angular Velocity, Velocity (Body and World), Position, Raw Data of INS / GNSS / VMS incl. time-stamp, internal status information	
Performance:	True Heading:	< 0.05° with at least single antenna GNSS (data fusion) ² and (no dual antenna required)
		< 0.04° with RTK corrections ² ; < 0.02° with RTK post-proc
		< 0.2° ¹ with 1 m baseline between the two GNSS antennas (-DA)
		< 0.1° ¹ with 2 m baseline between the two GNSS antennas (-DA)
	Roll/Pitch Accuracy:	< 0.05° with GNSS, 0.02° with RTK; S/A off; < 0.005° RTK post-proc
	Position accuracy:	1...2 m with GPS, S/A off
		0.6 m with SBAS
		0.02 m with RTK corrections online or with RTK post-proc
	Dead-Reckoning:	< 0.2 % [CEP] of distance travelled in lon/lat and altitude (with wheel sensor)
	Velocity:	< 0.05 m/s with GNSS; < 0.01 m/s with RTK
Altitude:	1...4 m with GNSS, S/A off	
	0.06 m with RTK corrections online or with RTK post-proc	
Alignment Time:	< 3 min. GNSS cold start, < 90 sec GNSS warm start; < 30 sec with stored heading	
Inertial Sensor Performance:	<u>Gyroscopes</u>	<u>Accelerometers</u>
Range:	± 490 °/s (no angle limitation)	± 15 g
Gyro ARW, Accel. Noise:	< 0.1 deg/√h	< 100 µg/√Hz
Linearity / Scalefactor:	0.05 % / 0.05 %	50 µg/g ² / 0.15 %
Drift (unaided), Accel. Offset:	< 5 °/hr	< 2 mg
Bias Stability (AV):	< 0.1 °/hr	< 50 µg
Bias (filtered ²):	< 1 °/h	< 0.5 mg
Resolution of Raw Data:	< 0.5 µrad / LSB	< 0.1 µg / LSB
Axis Misalignment:	< 0.5 mrad	< 0.5 mrad
GNSS Receiver (integrated):	up to all frequency GPS+GLONASS+GALILEO+BEIDOU, RTK/PPP, L-Band; high speed range version (< 515 m/s) available as option (iNAT-MSLG-HRS, requires export license)	
Input Interfaces (options):	external GNSS receiver (standard: integrated GNSS receiver); event trigger (PPS / SYNC, RS422 level), odometer (opto-coupler input up to 32 V, A/B quadrature or counts & direction, RS422 level compliant)	
Output Interfaces (options):	UART RS232/422, Ethernet TCP/IP / UDP, CAN, ARINC429, ARINC825, HDLC/SDLC, PPT (Pulse per Time), PPS, SYNC; PTP / NTP Server (since HW rev. 4); NTRIP caster; PPD (Pulse-per Distance)	
Data Output Rate:	1...500 Hz, internal data rate 1'000 Hz	
Data Latency and Jitter:	1.3 ms (sampling accuracy better 1 µs, time-stamped according to PPS; jitter < 1 ms)	
Data storage:	32 GByte on internal non-volatile memory (option: 128 GByte)	
Atomic Clock TimeRef. (opt.):	external high precision clock, drift < 100 ps/s (= 90 µs / 10 days) for -15...+55 °C ambient temperature	
Connectors:	MIL-C-38999 Series III for signals and power, TNC for antenna	
Temperature, rel. Humidity:	-55...+70 °C operating (case), +85 °C short term operation (30 min.); -55...+85°C storage; 8...100% rel. humidity; IP67 protection level [the industrial version with -40...+63 °C operating is fully RoHS compliant]	
Acoustic Noise Level Prot.:	up to 140 dB	
MTBF / MTTR:	> 35,000 hrs (estimated for surveying applications) / < 30 minutes	
Shock, Vibration, Altitude:	6 g / 20 ms operational and 40 g / 15 ms non-operational; 40 g / 20 ms crash safety; 4.1 g rms (operating) and 6 g rms (endurance) [10...2'000 Hz]; 60'000 ft	
Qualification:	designed to meet MIL-STD-810G, MIL-STD-461G, MIL-STD-704F, DO160G (qualification on request)	
Power:	10...35 V DC, < 25 W (incl. GNSS); 50 ms hold up time according to DO160; continuous overvoltage protection up to 60 V	
Weight / Size:	approx. 5.1 kg / approx. 187 x 130 x 261 mm ³ (WxHxL), w/o connectors;	
Installation:	Installation in all arbitrary orientations allowed; both antennas in -DA setup to see the same satellites	
Software:	iXCOM communication protocol; iXCOM-CMD GUI software under MS Windows and Linux available; INS/GNSS post-proc iWP+ / iIP+; integrated real-time Kalman filter (42+ states); on request customized applications can be integrated	

iMAR Navigation manufactures and designs inertial navigation, surveying, guidance, control and stabilization systems for defence, airborne, industrial, automotive, agriculture, mining, drilling, surveying and many other applications. All systems are manufactured and maintained by iMAR Navigation in Europe / Germany.

iMAR Navigation GmbH • Im Reihersbruch 3 • D-66386 St. Ingbert / Germany

Phone: +49-(0)-6894-9657-0 • Fax: +49-(0)-6894-9657-22

www.imar-navigation.de • sales@imar-navigation.de

¹ initial heading accuracy obtained from dual-antenna setup only; will be automatically improved as soon as certain motion is observed (given values valid for sufficient GNSS availability and environment)

² after algorithm converging under sufficient motion dynamics with suffic. GNSS aiding, during constant temperature

